

10/572,782

gn 11/1/2010

On page 5, please amend the third and fourth paragraphs as follows:

It is also provided that the first through opening 34 has an angular spacing  $\alpha$  ~~[[a]]~~ from the center line 43 and the second through opening 37 has an angular spacing  $\beta$  ~~[[b]]~~ from the center line 43, and the ratio between  $\beta$  ~~[[b]]~~ and  $\alpha$  ~~[[a]]~~ is between 5.2 and 6.0, and in a second approximation preferably between 5.4 and 5.6. A ratio of 5.5 has proved to be an ideal value. As a reference point for determining the angle, the location of the generator axis, that is, the axis of rotation of the rotor, is intended.

In a further feature of the invention, it is provided that between the second through opening 37 and the wiper contact mounting region 16, there is a further fastening point 84 ~~[[46]]~~, whose spacing from the second through opening 37 is between 11 mm and 36 mm. In a second approximation, a spacing c of between 25 mm and 33 mm is preferred. In a third approximation, a value between 28 mm and 31 mm is provided. The third fastening point 84 is accordingly intended as a so- called (B+) terminal.

On page 6, please delete the paragraph contained in lines <sup>25-29</sup>~~26-29~~ in its entirety. gn 11/1/2010

Please amend the paragraph bridging pages 6-7 as follows: